

DARRAH's

Air Cooled Plating & Anodizing SCR Controlled Rectifiers



DARRAH ELECTRIC COMPANY, a leading manufacturer of custom built rectifier equipment since 1960, announces its new line of AIR COOLED RECTIFIERS. Our rectifiers are engineered and designed to withstand the humid and corrosive atmosphere common in the plating environment. Component selection and part location is of great importance to ensure reliable performance.

SOLID STATE SCR CONTROLLED RECTIFIERS

feature independent voltage and current adjustments and provide $\pm 1\%$ DC voltage regulation with current limit and $\pm 1\%$ DC current regulation with voltage limit.

SOLID STATE CONTROLLED MODELS

can be connected to computers or process control systems, and are found in small laboratory models as well as large production Power Supplies. Rectifiers can be supplied to operate with inboard controls or from a remote controlled station.

Cooling

Small power supplies can be natural convection cooled. Forced air cooling with fans or blowers is common in larger sizes. For harsh, corrosive or high temperature environments, water cooling is best suited.

Silicon Diodes

Darrah's diodes are rated at 300 amperes, 600 peak inverse volts. Six are used per 1000 amperes of the rectifier's DC rating. Diode currents are balanced to within 5%.

Diode Heat Sinks

Diodes are directly mounted to a copper strap, not to the heat sink. The unique aluminum heat sink features 195 sq. in. of heat transfer to maintain the most efficient operating temperature.

Copper DC Output Bus

Individual Diode Fuses

Calibrated DC Shunt

Exhaust Fan

A polypropylene fan blade is utilized, specifically designed to resist dirt buildup and last for years. The fan motor is three phase, totally enclosed, and lubricated for five years usage.

Sealed Side Mounted Control Enclosure

Finish

Two part polyurethane provides exceptional resistance to the environment. Available in all popular colors.

Cabinet

Heavy duty steel construction.

Power Transformer

Darrah manufactures its transformers to our own rigorous specifications. Each transformer has isolated primary and secondary windings and are wound with all copper wires. The transformer is rated at NEMA class "H." Each transformer is designed and tested to provide continuous nameplate rating.



SEALED SIDE MOUNTED CONTROL ENCLOSURE

- Environmentally sealed
- Convenient location for:
 - Terminal connections
 - Printed circuit boards
 - AC line and DC overload devices
 - Fuses and Overloads
 - SCR control connections
 - Maintenance and servicing

SCR Firing Board

- Common industry standard
- Digital LSI technology
- High quality keyed quick disconnect plugs and jacks
- Operational status indicating lights
- Not phase sensitive

Step Down Voltage Control Transformer

SCR Modules

With through-the-wall design. Sensitive electrical connections are located in sealed side enclosure, eliminating short circuits commonly found in humid environments.

Terminal Strip

For remote control connections.

Control Circuit Fuses

AC Line Contactor

Fan Fuses

Fast Response DC Overload



Popular Darrah Rectifier Options

PLC Interfacing and Controlling

Darrah offers a four channel PLC interface. Two channels control the DC output current and voltage. Two monitor the voltage and current. Use PLC or processes controllers to start or stop the rectifier, initiate ramp cycles, and timer functions. Monitor safety circuits and alarms.

Digital LED Meters

.5" high display, available with NEMA rated clear sealed covers.

Ampere Time Meters

Accurately record coating thickness over time. Available in preset or totalizing counters.

Batch or Cycle Timers

Unlimited number of uses available in seconds, minutes or hours.

Internal DC Polarity Reversing

Manual or automatic controls.

PLC Programming

Control DC output current and voltages. Start processes or polarity reverse.

Adjustable DC Voltage Ramp Control

Repeatable accuracy in processes requiring a preset DC voltage rise over an adjustable time period.

Ripple Filtering

Available to maximum 5%, 2%, and 1% throughout entire DC output range.

Adjustable Transformer Taps

Improve efficiency and electrical cost savings with selected voltage taps. Unlimited choices available.

Custom Enclosures

Special enclosure shape or size. Multiple independent units in one cabinet.

Air Filters

Washable aluminum or stainless steel air filters.

12 Pulse Designs

High efficiency, ultra low output ripple, lower harmonics.

Remote Control Enclosure

Sealed thermoplastic remote enclosures can house single or multiple rectifier controls. Exceptional chemical resistance meets NEMA 12 and NEMA 4X requirements.

LED DC Ammeter and Voltmeter

.5" high display, 1% accuracy, with sealed covers.

Manual Polarity Reversing Switch

With forward and reverse indicating pilot lights.

Digital Process Timers

Adjustable between .01 seconds and 999 hours.

Individual Constant Voltage and Current Controls

Start and Stop Push Buttons

1" oil tight.



Standard Protection and Safety Circuits

- AC Line Fuses
- Start and stop control circuits stepped down to 115 volts. Includes isolation transformer with primary and secondary fuses.
- AC Line phase loss and phase imbalance protection.
- AC Line Contactor
- Thermostats located in strategic areas as power transformer, SCR's, diodes, and heat sinks.
- Fan or blower fuse protection.
- DC current and DC voltage limit controls.
- Fast response electronic DC overload protection.
- Diode and SCR fuse protection available with blown fuse indicators.

Input Line Requirements

208 through 600 volts, 3 phase, 50 or 60 hertz. Smaller production models can be ordered with all common single phase AC line inputs.

Duty Cycle

All models are designed to be operated at 100% nameplate rating continuously at 40°C ambient.

Warranty

Warranty on all components and workmanship is one year.



DARRAH ELECTRIC COMPANY

5914 MERRILL AVENUE • CLEVELAND, OHIO 44102

Toll Free 800-621-0014 Cleveland 216-631-0912 Fax 216-631-0440 E-mail decdarrah@earthlink.net

www.darrahelectric.com

