

Quantity	Quantity
Discounts:	0-4
	5-24
	25-49
	50-99
	100-249
	250-499

Package Type: Each

Units Per 1

Package:

Product Details:

Action At Setpoint: Open

Open F: 220 +/-5

Close F: 190 +/-10

Mounting: Surface Mount

Terminals: Solder Tab

Orientation From Mount 45 Degrees

Holes:

Electrical ratings - Type S: 125VAC, 15 Amps, Resistive
250VAC, 10 Amps, Resistive
100,000 cycles

Inductive load ratings: 120VAC, 5.8FLA, 34.8LRA
240VAC, 2.9FLA, 17.4LRA
6,000 cycles

Electrical ratings - Type K: 30VDC, 1 Amp, Resistive
120VAC, 125VA (Pilot Duty)
100,000 cycles@I Other

Operating Temperature: 50 - 320 Degrees F (10-160 Degrees C)

Differential: 15 - 100 Degrees F (8 - 56 Degrees C)

Environmental Temperature: 32 - 350F (0 - 177 Degrees C)

Insulation Resistance: 100M ohms or more (with a 500VDC megger)

Circuit Resistance: 50m ohms or less (initial value)

Dielectric Strength: 1,500VAC / 1 Minute

Approvals: UL File No. E145478(S), XAPX2, CUL File No. E145478(S), XAPX8, CSA File No. LR63201, VDE File No. 69046, Demko File No. DK-45I

Minimum Order Quantity: 2