Powerex, Inc., 200 Hillis Street, Youngwood, Pennsylvania 15697-1800 (724) 925-7272

Dual IGBTMOD™ H-Series Module
150 Amperes/600 Volts



Outline Drawing and Circuit Diagram

Dimensions	Inches	Millimeters
A	3.70	94.0
B	3.150±0.01	80.0±0.25
C	1.89	48.0
D	1.18 Max.	30.0 Max.
E	0.90	23.0
F	0.83	21.2
G	0.71	18.0
H	0.67	17.0
J	0.63	16.0

Dimensions	Inches	Millimeters
K	0.51	13.0
L	0.47	12.0
M	0.30	7.5
N	0.28	7.0
P	0.256 Dia.	Dia. 6.5
Q	0.26	6.5
R	M5 Metric	M5
S	0.16	4.0

Description:
Powerex IGBTMOD™ Modules are designed for use in switching applications. Each module consists of two IGBT Transistors in a half-bridge configuration with each transistor having a reverse-connected super-fast recovery free-wheel diode. All components and interconnects are isolated from the heat sinking baseplate, offering simplified system assembly and thermal management.

Features:
- ☐ Low Drive Power
- ☐ Low $V_{CE(sat)}$
- ☐ Discrete Super-Fast Recovery (70ns) Free Wheel Diode
- ☐ High Frequency Operation (20-25kHz)
- ☐ Isolated Baseplate for Easy Heat Sinking

Applications:
- ☐ AC Motor Control
- ☐ Motion/Servo Control
- ☐ UPS
- ☐ Welding Power Supplies
- ☐ Laser Power Supplies

Ordering Information:
Example: Select the complete part module number you desire from the table below -i.e. CM150DY-12H is a 600V (V_{CES}), 150 Ampere Dual IGBTMOD™ Power Module.

Type	Current Rating Amperes	V_{CES} Volts (x 50)
CM	150	12

Powerex, Inc., 200 Hillis Street, Youngwood, Pennsylvania 15697-1800 (724) 925-7272

CM150DY-12H
Dual IGBTMOD™ H-Series Module
150 Amperes/600 Volts

Authorized Distributor:
Darrah Electric Company
www.darrahelectric.com

Absolute Maximum Ratings, T_j = 25 °C unless otherwise specified

Ratings	Symbol	CM150DY-12H	Units
Junction Temperature	T_j	–40 to 150	°C
Storage Temperature	T_{stg}	–40 to 125	°C
Collector-Emitter Voltage (G-E SHORT)	V_{CES}	600	Volts
Gate-Emitter Voltage	V_{GES}	±20	Volts
Collector Current	I_C	150	Amperes
Peak Collector Current	I_{CM}	300*	Amperes
Diode Forward Current	I_F	150	Amperes
Diode Forward Surge Current	I_{FM}	300*	Amperes
Power Dissipation	P_d	600	Watts
Max. Mounting Torque M5 Terminal Screws	–	17	in-lb
Max. Mounting Torque M6 Mounting Screws	–	26	in-lb
Module Weight (Typical)	–	270	Grams
V Isolation	V_{RMS}	2500	Volts

* Pulse width and repetition rate should be such that device junction temperature does not exceed the device rating.

Static Electrical Characteristics, T_j = 25 °C unless otherwise specified

Characteristics	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Collector-Cutoff Current	I_{CES}	$V_{CE} = V_{CES}$, V_{GE} = 0V	–	–	1.0	mA
Gate Leakage Current	I_{GES}	$V_{GE} = V_{GES}$, V_{CE} = 0V	–	–	0.5	μA
Gate-Emitter Threshold Voltage	$V_{GE(th)}$	I_C = 15mA, V_{CE} = 10V	4.5	6.0	7.5	Volts
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	I_C = 150A, V_{GE} = 15V	–	2.1	2.8**	Volts
		I_C = 150A, V_{GE} = 15V, T_j = 150°C	–	2.15	–	Volts
Total Gate Charge	Q_G	V_{CC} = 300V, I_C = 150A, V_{GS} = 15V	–	450	–	nC
Diode Forward Voltage	V_{FM}	I_E = 150A, V_{GS} = 0V	–	–	2.8	Volts

** Pulse width and repetition rate should be such that device junction temperature rise is negligible.

Dynamic Electrical Characteristics, T_j = 25 °C unless otherwise specified

Characteristics		Symbol	Test Conditions	Min.	Typ.	Max.	Units
Input Capacitance		C_{ies}	V_{GE} = 0V, V_{CE} = 10V, k = 1MHz	–	–	15	nF
Output Capacitance		C_{oes}		–	–	5.3	nF
Reverse Transfer Capacitance		C_{res}		–	–	3	nF
Resistive	Turn-on Delay Time	$t_{d(on)}$	V_{CC} = 300V, I_C = 150A, $V_{GE1} = V_{GE2}$ = 15V, R_G = 4.2Ω	–	–	200	ns
Load	Rise Time	t_r		–	–	550	ns
Switching	Turn-off Delay Time	$t_{d(off)}$		–	–	300	ns
Times	Fall Time	t_f		–	–	300	ns
Diode Reverse Recovery Time		t_{rr}	I_E = 150A, di_E/dt = –300A/μs	–	–	110	ns
Diode Reverse Recovery Charge		Q_{rr}	I_E = 150A, di_E/dt = –300A/μs	–	0.41	–	μC

Thermal and Mechanical Characteristics, T_j = 25 °C unless otherwise specified

Characteristics	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Thermal Resistance, Junction to Case	$R_{th(j-c)}$	Per IGBT	–	–	0.21	°C/W
Thermal Resistance, Junction to Case	$R_{th(j-c)}$	Per FWDi	–	–	0.47	°C/W
Contact Thermal Resistance	$R_{th(c-f)}$	Per Module, Thermal Grease Applied	–	–	0.065	°C/W

CM150DY-12H
Dual IGBTMOD™ H-Series Module
150 Amperes/600 Volts

OUTPUT CHARACTERISTICS (TYPICAL)



TRANSFER CHARACTERISTICS (TYPICAL)



COLLECTOR-EMITTER SATURATION VOLTAGE CHARACTERISTICS (TYPICAL)



COLLECTOR-EMITTER SATURATION VOLTAGE CHARACTERISTICS (TYPICAL)



FREE-WHEEL DIODE FORWARD CHARACTERISTICS (TYPICAL)



CAPACITANCE VS. V_{CE} (TYPICAL)



HALF-BRIDGE SWITCHING CHARACTERISTICS (TYPICAL)



REVERSE RECOVERY CHARACTERISTICS (TYPICAL)



GATE CHARGE, V_{GE}



Authorized Distributor:
Darrah Electric Company
www.darrahelectric.com

CM150DY-12H
Dual IGBTMOD™ H-Series Module
150 Amperes/600 Volts





Darrah Electric Company
5914 Merrill Avenue
Cleveland, OH 44102 USA
216-631-0912
216-631-0440 fax
www.darrahelectric.com